POWERED BY Dialog

LIQUID CRYSTAL DISPLAY DEVICE (04-253033 Publication Number: JP 4253033 A), September 08, 1992

Inventors:

- YANO SHINICHI
- TAKAHASHI HIDEKI

Applicants

• SANYO ELECTRIC CO LTD (A Japanese Company or Corporation), JP (Japan)

Application Number: 03-010174 (JP 9110174), January 30, 1991

International Class (IPC Edition 5):

- G02F-001/136
- G02F-001/1343
- H01L-027/12
- H01L-021/336
- H01L-029/784

JAPIO Class:

- 29.2 (PRECISION INSTRUMENTS--- Optical Equipment)
- 42.2 (ELECTRONICS--- Solid State Components)

JAPIO Keywords:

- R011 (LIQUID CRYSTALS)
- R096 (ELECTRONIC MATERIALS--- Glass Conductors)

Abstract:

PURPOSE: To improve the yield by forming a source electrode and a display electrode, and a drain electrode and a drain line integrally of ITO and electrically connecting them.

CONSTITUTION: Plural drain lines 44 and gate lines 35 are formed on a transparent insulating substrate and switching elements 45 of TFTs and display electrodes 50 are formed in matrix at their intersections. The display electrode 5 is formed from an amorphous silicon contact layer corresponding to a source and the drain line 44 is formed of the material of the display electrode 50 from an amorphous silicon contact layer corresponding to a drain. Therefore, the source electrode and display electrode 50, and drain electrode and drain line 44 are formed continuously of ITO, so a defect due to pattern deviation of photolithography, etc., is eliminated and the constitution part of the liquid crystal display device is prevented from deviating accompanying the subminiaturization of elements. (From: *Patent Abstracts of Japan*, Section: P, Section No. 1473, Vol. 17, No. 33, Pg. 97, January 21, 1993)

JAPIO

© 2003 Japan Patent Information Organization. All rights reserved. Dialog® File Number 347 Accession Number 3887933